

## Modul<sup>®</sup> flexible

**Description:** The insulation is made of EPS with graphite particles and polyester nonwoven. Delivered in preformed shells with a tongue and groove connection and a surface made of flexible PVC with a layer of PU soft foam.

**Application:** The components are designed as insulation on hot water tanks, and allow to reach energy efficiency class B or C. These tanks are supposed to be installed indoors, for example in utility rooms, cellars, boiler rooms, heated garages or other frost free spaces. Ideal operating temperature is between 35°C and 95 °C of the tank.



### Technical specification

Thermal conductivity EPS	≤ 0,032	W/mK
--------------------------	---------	------

Thermal conductivity polyester nonwoven	≤ 0,038	W/mK
-----------------------------------------	---------	------

Density	ca. 15	kg/m <sup>3</sup>
---------	--------	-------------------

Fire class	B2	
------------	----	--

Temperature resistance (long/short)	95/120	°C
-------------------------------------	--------	----

Thickness	80 - 160	mm
-----------	----------	----

Surface	PVC + 5 mm PU soft foam	
---------	-------------------------	--

### Quality, Environment & Safety

No harmful substances concerning EU regulation 91/155/EEC

Free of HBCD and substances on RoHS-, REACH, and GADSL lists



The information is based on today's knowledge and experience at the time of creation. If not expressly declared, it is not a warranty according to the spirit of the law.

17.11.2019